



# Selection and ordering data

## Type 2RB 920

No.	Fre- quency	Rated			Max. differential pressure <sup>1)</sup>		Sound pressure level <sup>2)</sup>	Weight Approx.	Order No.
		Voltage	Current	Power	Vacuum	Pressure			
		Hz	V	A	kW	mbar			
<b>3~ 50/60 Hz, IP55, Insulation material class F, IE2</b>									
1	50	350 - 450 Δ / 610 - 725 Y	22.00 Δ / 12.7 Y	11	-240	220	74	190	<b>2RB 920-7HT17</b>
	60	400 - 500 Δ / 690 - 725 Y	22.00 Δ / 12.9 Y	12.6	-160	140	84		
2	50	350 - 450 Δ / 610 - 725 Y	30.50 Δ / 17.3 Y	15	-360	330	74	198	<b>2RB 920-7HT27</b>
	60	400 - 500 Δ / 690 - 725 Y	29.50 Δ / 17.0 Y	17.3	-300	260	84		
3	50	350 - 450 Δ / 610 - 725 Y	37.00 Δ / 21.0 Y	18.5	-440	430	74	204	<b>2RB 920-7HT37</b>
	60	400 - 500 Δ / 690 - 725 Y	36.50 Δ / 21.0 Y	21.3	-420	370	84		

5HOLHIBOMDDBLODEOHIBOLPLVQLIIHUHDDOSUHMH

0HDMLEIDFHEISUHHOHOHMODFFW,62PHDMHGZBETKBOHDDGLMGR7KSRSLV  
SLSLGRFWGEMHOLHIBOMLWGDHUDEHG%

WMBHGDMUDHUKUHUHMHW

0O5BLOW(BDFKBUDQ(0BDMGLUHFWMDQM(1BP5MWOHFWLFDQ

PDFKEV

7KPBFRSOZW,(BGMUPDOFODY

7KDDHHDUDELV

7KIUHTNEDHUDELVDP

## Other voltages

50 Hz	50 Hz voltage range	60 Hz voltage range	86 Hz (5000 rpm)	100 Hz (6000 rpm)	25%...-7.5%	
<b>3- IE2</b>						
9	9<	9 9<	9 9<		9	7
9	'	9	9			7
9	' 9<	9 9<	9 9<	9		7
9	' 9<	9 9<	9 9<			7
<b>3-,(</b>						
	9 9<	9 9<	9	9		H 1
	9 9<	9 9<				H 6
	9	9				H 7
	9	9				C 5

3HUIBPDHFDGLIIHULIWDUGPDDUHMGC3OHDMUHIIHURBUH3QLQDDMHW



Changes in particular of the quoted performance curve, data and weights may occur without prior notice. The data given do not constitute an obligation from our side to deliver as shown.

**GREENCO**®

<RXU 8OWLDPDW 6RXUFH IRU 9DFXXP DQG 3UHVXXUH

=+(-,\$1\* \*5((1&2 ,1'8675< &2 /7'  
5RQJVKL 5RDG 'DQ\D ,QGXWULDO =RQ  
7RZQ :HQOLQJ &KLQD  
7HO  
)D[  
ZZZ JUHHQFR FQ  
( PDLO JUHHQFR#JUHHQFR FQ